

14078 Meridian Parkway, Riverside, CA. 92518

SAFETY DATA SHEET

Version: v1

Revision Date: 2024-01-16

Print Date: 2024-01-21

SECTION 1:Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Isobutyllithium solution

Product Number : I114513
Brand : aladdin
CAS-No. : 920-36-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances.

1.3 Company

Company : ALADDIN SCIENTIFIC CORPORATION

Address : 14078 Meridian Parkway,

Riverside, CA. 92518

Telephone : +1 (833) 552-7181 Fax : no data available

1.4 Emergency telephone number

CHEMTREC®, Inside the USA : 1-800-424-9300

CHEMTREC®. Outside the USA :

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

2.2 GHS Label elements, including precautionary statements

Pictogram



Danger









Signal word

Hazard statement(s)

H225 Highly Flammable liquid and vapor

H304 May be fatal if swallowed and enters airways
H314 Causes severe skin burns and eye damage

H336 May cause drowsiness or dizziness

H410 Very toxic to aquatic life with long lasting effects

Precautionary statement(s)



14078 Meridian Parkway, Riverside, CA. 92518

P210 Keep away from heat, hot surface, sparks, open flames and other ignition

sources. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses if present and easy to do - continue rinsing.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Lithium 2-methyl-1-propanide

Formula : C4H9Li
Molecular weight : 64.06
CAS No. : 920-36-5

EC-NO. : no data available

Component	Classification	Concentration
Isobutyllithium solution		
	no data available	1.6M in n-hexane

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

no data available



14078 Meridian Parkway, Riverside, CA. 92518

4.3 Indication of any immediate medical attention and special treatment needed

no data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media

no data available

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition products formed under fire conditions.- Carbon oxides, Lithium oxides

5.3 Advice for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so.Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

no data available

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.



14078 Meridian Parkway, Riverside, CA. 92518

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Recommended storage temperature: 2 - 8 °C Store under inert gas. Moisture sensitive.

7.3 Specific end use(s)

no data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

no data available

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearanceb) Odourc) Odour Thresholdno data availableno data available



14078 Meridian Parkway, Riverside, CA. 92518

d) pH	no data available
e) Melting point/freezing point	no data available
f) Initial boiling point and boiling range	no data available
g) Flash point	-4 °C
h) Evaporation rate	no data available
i) Flammability (solid, gas)	no data available
j) Upper/lower flammability or	
explosive limits	no data available
k) Vapour pressure	no data available

I) Vapour density no data available m) Relative density no data available n) Water solubility no data available o) Partition coefficient: n-octanol/water no data available no data available p) Auto-ignition temperature q) Decomposition temperature no data available no data available r) Viscosity s) Explosive properties N no data available t) Oxidizing properties N no data available

9.2 Other safety information

no data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapours may form explosive mixture with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

no data available

10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions.- Carbon oxides, Lithium oxides

SECTION 11: Toxicological information



14078 Meridian Parkway, Riverside, CA. 92518

11.1 Information on toxicological effects

Acute toxicity

no data available

Skin corrosion/irritation

no data available

Serious eye damage/eye irritation

no data available

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

no data available

Specific target organ toxicity - single exposure

no data available

Specific target organ toxicity - repeated exposure

no data available

Aspiration hazard

May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract. Vapours may cause drowsiness and dizziness

Additional Information

no data available

SECTION 12: Ecological information

12.1 Toxicity

no data available

12.2 Persistence and degradability

no data available

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.



14078 Meridian Parkway, Riverside, CA. 92518

12.6 Other adverse effects

no data available

SECTION 13:

13.1 Disposal considerations

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 3394 Packing group: I Class: 4.2 (4.3)

Proper shipping name: Organometallic Reportable Quantity(RQ): no data Poison Inhalation Hazard: no data

substance, liquid, pyrophoric, water- available available

reactive (Heptane, Isobutyllithium)

Environmental Hazards: No

IMDG

UN number: 3394 Packing group: I EMS-No: no data available Proper shipping name: Organometallic substance, liquid, pyrophoric, water-reactive (Heptane, Isobutyllithium)

IATA

UN number: 3394 Packing group: I Class: 4.2 (4.3)

Proper shipping name: Organometallic substance, liquid, pyrophoric, water-reactive (Heptane, Isobutyllithium)

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

SECTION 16: Other information

Regulatory Affairs

Prepared By ALADDIN SCIENTIFIC CORPORATION

Email: QualityAssurance@aladdinsci.com

Creation Date10-Sep-2020Revision Date16-Jan-2024Print Date21-Jan-2024

Revision Summary SDS sections updated v1



14078 Meridian Parkway, Riverside, CA. 92518

Disclaimer

Copyright Aladdin Co. Ltd. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Aladdin Co. Ltd. and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.