

14078 Meridian Parkway, Riverside, CA. 92518

SAFETY DATA SHEET

Version: v1

Revision Date: 2024-02-04

Print Date: 2024-02-04

SECTION 1:Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Lithium chloride solution

Product Number : L433503 Brand : aladdin

CAS-No. : 7447-41-8(Ethanol)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances.

1.3 Company

Company : ALADDIN SCIENTIFIC CORPORATION

Address : 14078 Meridian Parkway,

Riverside, CA. 92518

Telephone : +1 (833) 552-7181 Fax : no data available

1.4 Emergency telephone number

CHEMTREC®, Inside the USA : 1-800-424-9300

CHEMTREC®. Outside the USA :

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquid (Class 2), H225

Skin corrosion/irritation (Category 3), H316

Severe eye injury/eye irritation (Category 2A), H319

2.2 GHS Label elements, including precautionary statements

Pictogram



Danger



Signal word

Hazard statement(s)

H225 Highly Flammable liquid and vapor

H316 Causes mild skin irritation

H319 Causes serious eye irritation



14078 Meridian Parkway, Riverside, CA. 92518

Precautionary statement(s)	
P210	Keep away from heat, hot surface, sparks, open flames and other ignition
	sources No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting//] equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash hands [and] thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN
	with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses if present and easy to do - continue rinsing.
P332+P313	IF SKIN irritation occurs: Get medical advice/attention.
P337+P313	IF eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : no data available

Formula : LiCl Molecular weight : 42.39

CAS No. : 7447-41-8(Ethanol)

EC-NO. : 231-212-3

Component	Classification	Concentration
Lithium chloride solution		
	no data available	1 M in ethanol

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled



14078 Meridian Parkway, Riverside, CA. 92518

Move the victim into fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration and consult a doctor immediately. Do not use mouth to mouth resuscitation if the victim ingested or inhaled the chemical.

In case of skin contact

Take off contaminated clothing immediately. Wash off with soap and plenty of water. Consult a doctor.

In case of eye contact

Rinse with pure water for at least 15 minutes. Consult a doctor.

If swallowed

Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Center immediately.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

no data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use dry chemical, carbon dioxide or alcohol-resistant foam.

Unsuitable extinguishing media

no data available

5.2 Special hazards arising from the substance or mixture

Carbon oxides Hydrogen chloride gas Lithium oxide Combustible Be careful of tempering. Vapour is heavier than air, so it can spread across the ground. When a fire occurs, it may cause the production of hazardous gases or vapors Forming explosive mixtures with air at mild temperatures

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

no data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing mist, gas or vapours. Avoid contacting with skin and eye. Use personal protective equipment. Wear chemical impermeable gloves. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions



14078 Meridian Parkway, Riverside, CA. 92518

Prevent further spillage or leakage if it is safe to do so. Do not let the chemical enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Collect and arrange disposal. Keep the chemical in suitable and closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Operators should be specially trained and strictly abide by the operating procedures. Operation and disposal should be carried out in a place with local ventilation or general ventilation facilities. Avoid eye and skin contact and avoid breathing vapor. See Section 8 for personal protective measures. Keep away from fire and heat sources, and smoking is strictly prohibited in the workplace. Use explosion-proof ventilation systems and equipment. If canning is required, the flow rate should be controlled, and there should be a grounding device to prevent the accumulation of static electricity. Avoid contact with incompatible substances such as oxidizing agents (see section 10 for incompatible substances). When handling, it should be lightly loaded and unloaded to prevent damage to packaging and containers. Empty containers may be harmful residues. Wash hands after use and prohibit eating or drinking in the workplace. Equipped with the corresponding variety and quantity of fire fighting equipment and leakage emer

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool and ventilated warehouse.

7.3 Specific end use(s)

no data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN166(EU).



14078 Meridian Parkway, Riverside, CA. 92518

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. The selected protective gloves have to satisfy the specifications of Regulation (EU)2016/425 and the standard EN 374 derived from it.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a fullface particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection,use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN(EU).

Control of environmental exposure

If safety requires, prevent further leakage or spillage. Do not let the product enter the sewer.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance form, Liquid Color, Color	form: Liau	Appearance form: Liquid o	color: Colorless
---	------------	---------------------------	------------------

b) Odour no data available c) Odour Threshold no data available d) pH no data available e) Melting point/freezing point no data available f) Initial boiling point and boiling range no data available g) Flash point no data available no data available h) Evaporation rate i) Flammability (solid, gas) no data available

j) Upper/lower flammability or explosive limits no data available k) Vapour pressure no data available I) Vapour density no data available m) Relative density 0.83g/mLat 20°C n) Water solubility no data available o) Partition coefficient: n-octanol/water no data available p) Auto-ignition temperature no data available q) Decomposition temperature no data available no data available r) Viscosity s) Explosive properties N no data available t) Oxidizing properties N no data available



14078 Meridian Parkway, Riverside, CA. 92518

9.2 Other safety information

no data available

SECTION 10: Stability and reactivity

10.1 Reactivity

no data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

no data available

10.4 Conditions to avoid

Heating

10.5 Incompatible materials

Alkali metals, ammonia, peroxides, strong acids, strong oxidants, bromine trifluoride

10.6 Hazardous decomposition products

no data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral: No data available

Acute toxicity estimated orally ->5000 mg/kg

(Calculation method)

Symptoms: Possible symptoms: Mucosal irritation

Skin corrosion/irritation

no data available

Serious eye damage/eye irritation

no data available

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity



14078 Meridian Parkway, Riverside, CA. 92518

no data available

Specific target organ toxicity - single exposure

no data available

Specific target organ toxicity - repeated exposure

no data available

Aspiration hazard

no data available

Additional Information

High concentrations of lithium ions can cause dizziness and collapse, and limited sodium intake can cause kidney damage. Dehydration, weightlessness, skin effects, and thyroid function

Disorders have been reported. Possible central nervous system effects may include aphasia, blurred vision, loss of sensation, seizures, etc. Repeated exposure to lithium ions can

Suffering from diarrhea, vomiting, and neuromuscular effects such as tremors, cramps, and hyperreflexia., Babies breastfed by mothers treated with lithium carbonate will

The occurrence of pale disease and T-wave inversion, to our knowledge, has not been fully studied for its chemical, physical, and toxic properties., Central nervous system inhibition, malignant

Heart, headache, vomiting, anesthesia

Other dangers cannot be ruled out.

Operate according to good industrial hygiene and safety regulations.

SECTION 12: Ecological information

12.1 Toxicity

12.2 Persistence and degradability

no data available

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

no data available

12.6 Other adverse effects

no data available

SECTION 13:

13.1 Disposal considerations



14078 Meridian Parkway, Riverside, CA. 92518

Product

Recycle to process, if possible. Consult your local regional authorities and an expert of disposal. You may be able to dissolve or mix material with a combustible solvent and little by little burn in a chemical incinerator equipped with an afterburner and scrubber system. If a large amount of the substance is burned at a time, an explosion may occur. Observe all federal, state and local regulations when disposing of the substance.

Contaminated packaging
Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 1170 Packing group: II Class: 3

Proper shipping name: ETHANOL Reportable Quantity(RQ): no data Poison Inhalation Hazard: no data

SOLUTION available available

Environmental Hazards: no

IMDG

UN number: 1170 Packing group: II EMS-No: no data available

Proper shipping name: ETHANOL SOLUTION

IATA

UN number: 1170 Packing group: II Class: 3

Proper shipping name: ETHANOL SOLUTION

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

SECTION 16: Other information

Regulatory Affairs

Prepared By ALADDIN SCIENTIFIC CORPORATION

Email: QualityAssurance@aladdinsci.com

Creation Date04-Feb-2024Revision Date04-Feb-2024Print Date04-Feb-2024

Revision Summary SDS sections updated v1

Disclaimer

Copyright Aladdin Co. Ltd. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Aladdin Co. Ltd. and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.