

SAFETY DATA SHEET

Version: v1

Revision Date: 2025-09-14

Print Date: 2025-09-21

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Methyl acrylate
Product Number : M100032
Brand : aladdin
CAS-No. : 96-33-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances.

1.3 Company

Company : ALADDIN SCIENTIFIC CORPORATION
Address : 14078 Meridian Parkway,
Riverside, CA. 92518
Telephone : +1 (833) 552-7181
Fax : no data available

1.4 Emergency telephone number

CHEMTREC®, Inside the USA : 1-800-424-9300
CHEMTREC®, Outside the USA :

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225

Acute toxicity, Oral (Category 4), H302

Acute toxicity, Inhalation (Category 3), H331

Acute toxicity, Dermal (Category 4), H312

Skin corrosion/irritation (Category 2), H315

Serious eye damage/eye irritation (Category 2A), H319

Skin sensitization (Category 1), H317

Specific target organ toxicity - single exposure (Category 3), respiratory tract irritation,

H335

Short-term (acute) aquatic hazard (Category 2), H401

Long-term (chronic) aquatic hazard (Category 3), H412

2.2 GHS Label elements, including precautionary statements

Pictogram



Danger

Signal word

Hazard statement(s)

H225	Highly Flammable liquid and vapor
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H401	Toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects
H302+H312	Harmful if swallowed or in contact with skin

Precautionary statement(s)

P210	Keep away from heat, hot surface, sparks, open flames and other ignition sources. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting/...] equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash hands [and ...] thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P321	Specific treatment (see ... on this label).
P330	Rinse mouth.
P302+P352	IF ON SKIN: wash with plenty of water.
P303+P361+P353	IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

ALADDIN SCIENTIFIC CORPORATION

14078 Meridian Parkway, Riverside, CA. 92518

P333+P313	IF SKIN irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use ... to extinguish.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container to an approved waste disposal plant.
P264+P265	Wash hands [and ...] thoroughly after handling. Do not touch eyes.
P301+P317	IF SWALLOWED: Get medical help.
P317	Get emergency medical help.
P337+P317	If eye irritation persists: Get medical help.
P332+P317	If skin irritation occurs: Get medical help.
P319	Get medical help if you feel unwell.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms	: MA Methyl 2-propenoate Acrylic Acid Methyl Ester
Formula	: C ₄ H ₆ O ₂
Molecular weight	: 86.09
CAS No.	: 96-33-3
EC-NO.	: 202-500-6

Component	Classification	Concentration
Methyl acrylate	Flammable liquids Category 2; Acute toxicity Category 4; Acute toxicity Category 3; Acute toxicity Category 4; Skin corrosion/irritation Category 2; Serious eye damage/eye irritation Category 2A; Skin sensitization Category 1; Specific target organ toxicity - single exposure Category 3; Short-term (acute) aquatic hazard Category 2; Long-term (chronic) aquatic hazard Category 3; H225, H302, H331, H312, H315, H319, H317, H335, H401, H412	analytical standard, ≥99.5% (GC), Containing ≤ 100 ppm MEHQ stabilizer

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

no data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

no data available

5.2 Special hazards arising from the substance or mixture

Carbon oxides Combustible. Pay attention to flashback. Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Dispose of properly. Clean up affected area

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge. Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons. Sensitive to light, stored at room temperature in dark.

7.3 Specific end use(s)

no data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Component	CAS No.	Value	Control parameters	Basis
methyl acrylate	96-33-3	PC-TWA	20 mg/m3	Occupational exposure limits for hazardous factors in the workplace - chemical hazardous factors
	Note	Sensitive skin		

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment**Eye/face protection**

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

a) Appearance	form: Liquid color: Colorless
b) Odour	no data available
c) Odour Threshold	no data available
d) pH	no data available
e) Melting point/freezing point	-75°C
f) Initial boiling point and boiling range	80°C
g) Flash point	-3°C
h) Evaporation rate	no data available
i) Flammability (solid, gas)	no data available
j) Upper/lower flammability or explosive limits	no data available
k) Vapour pressure	no data available
l) Vapour density	no data available
m) Relative density	0.96
n) Water solubility	no data available
o) Partition coefficient: n-octanol/water	no data available
p) Auto-ignition temperature	no data available
q) Decomposition temperature	no data available
r) Viscosity	no data available

ALADDIN SCIENTIFIC CORPORATION

14078 Meridian Parkway, Riverside, CA. 92518

- | | |
|---------------------------|-------------------|
| s) Explosive properties N | no data available |
| t) Oxidizing properties N | no data available |

9.2 Other safety information

no data available

SECTION 10: Stability and reactivity

10.1 Reactivity

no data available

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion with: Peroxides Strong oxidizing agents Strong acids strong alkalis Activated charcoal

10.4 Conditions to avoid

Heat. May polymerize on exposure to light. Warming.

10.5 Incompatible materials

no data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity estimate Oral - 768 mg/kg

(Calculation method)

LD50 Oral - Rat - male - 768 mg/kg

(OECD Test Guideline 401)

Symptoms: Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract.

Acute toxicity estimate Inhalation - 4 h - 3 mg/l - vapor (Calculation method)

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of

ALADDIN SCIENTIFIC CORPORATION

14078 Meridian Parkway, Riverside, CA. 92518

respiratory tract

LC50 Inhalation - Rat - male and female - 4 h - < 10.8 mg/l - vapor

(OECD Test Guideline 403)

Acute toxicity estimate Dermal - 1,250 mg/kg

(Calculation method)

LD50 Dermal - Rabbit - 1,250 mg/kg

Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit Result: irritating - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit Result: Eye irritation Remarks: (IUCLID)

Respiratory or skin sensitisation

Local lymph node assay (LLNA) - Mouse Result: positive (OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Ames test Result: Not mutagenic in Ames Test. Remarks: (IUCLID) Test Type: Micronucleus test Species:

Mouse Cell type: Bone marrow Application Route: inhalation (vapor) Result: negative Remarks: (ECHA)

Carcinogenicity

no data available

Reproductive toxicity

no data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

no data available

Aspiration hazard

no data available

Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 90 d - NOAEL (No observed adverse

effect level) - 5 mg/kg - LOAEL (Lowest observed adverse effect level) - 20 mg/kg

Remarks: Subchronic toxicity

RTECS: AT2800000

Cough, Shortness of breath, Headache, Nausea, Vomiting, prolonged or repeated exposure

can cause:, Lung irritation

To the best of our knowledge, the chemical, physical, and toxicological properties have not

been thoroughly investigated.

Possible symptoms:

After absorption:

CNS disorders

Headache

Vomiting

somnolence

Damage to:

Liver

Lungs

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish flow-through test LC50 - *Oncorhynchus mykiss* (rainbow trout) - 3.4

mg/l - 96 h

(OECD Test Guideline 203)

flow-through test LC50 - *Cyprinodon variegatus* (sheepshead

minnow) - 1.1 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia flow-through test EC50 - *Daphnia magna* (Water flea) - 2.6 mg/l -and other aquatic

invertebrates

48 h

(OECD Test Guideline 202)

Toxicity to algae static test ErC50 - *Pseudokirchneriella subcapitata* (green algae) -

3.55 mg/l - 96 h

ALADDIN SCIENTIFIC CORPORATION

14078 Meridian Parkway, Riverside, CA. 92518

(OECD Test Guideline 201)

Toxicity to bacteria static test EC10 - activated sludge - > 100 mg/l - 72 h

Remarks: (ECHA)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d Result: 90 - 100 % - Readily biodegradable. (OECD Test Guideline 310)

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

no data available

12.6 Other adverse effects

no data available

SECTION 13:

13.1 Disposal considerations

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Discard as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 1919

Packing group: II

Class: 3

Proper shipping name: METHYL
ACRYLATE, STABILIZED

Reportable Quantity(RQ): no data
available

Poison Inhalation Hazard: no data
available

Environmental Hazards: no

IMDG

UN number: 1919

Packing group: II

EMS-No: no data available

Proper shipping name: METHYL ACRYLATE, STABILIZED

IATA

UN number: 1919

Packing group: II

Class: 3

Proper shipping name: METHYL ACRYLATE, STABILIZED

ALADDIN SCIENTIFIC CORPORATION

14078 Meridian Parkway, Riverside, CA. 92518

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

SECTION 16: Other information

Prepared By	Regulatory Affairs ALADDIN SCIENTIFIC CORPORATION Email: QualityAssurance@aladdinsci.com
Creation Date	08-Dec-2023
Revision Date	14-Sep-2025
Print Date	21-Sep-2025
Revision Summary	SDS sections updated v1

Disclaimer

Copyright Aladdin Co. Ltd. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Aladdin Co. Ltd. and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.