

14078 Meridian Parkway, Riverside, CA. 92518

SAFETY DATA SHEET

Version: v1

Revision Date: 2024-01-10

Print Date: 2024-01-11

SECTION 1:Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : n-Butyllithium solution

Product Number : N398264
Brand : aladdin
CAS-No. : 109-72-8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances.

1.3 Company

Company : ALADDIN SCIENTIFIC CORPORATION

Address : 14078 Meridian Parkway,

Riverside, CA. 92518

Telephone : +1 (833) 552-7181 Fax : no data available

1.4 Emergency telephone number

CHEMTREC®, Inside the USA : 1-800-424-9300

CHEMTREC®, Outside the USA :

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225

Pyrophoric liquids (Category 1), H250

Substances and mixtures which in contact with water emit flammable gases (Category 1), H260

Skin corrosion (Sub-category 1B), H314

Serious eye damage (Category 1), H318

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Aspiration hazard (Category 1), H304

Long-term (chronic) aquatic hazard (Category 2), H411



14078 Meridian Parkway, Riverside, CA. 92518

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Danger







Signal word

Hazard statement(s)

H225 Highly Flammable liquid and vapor

H250 Catches fire spontaneously if exposed to air

H260 In contact with water releases flammable gases which may ignite spontaneously

H304 May be fatal if swallowed and enters airways
H314 Causes severe skin burns and eye damage

H336 May cause drowsiness or dizziness

H411 Toxic to aquatic life with long lasting effects

Precautionary statement(s)

P210 Keep away from heat, hot surface, sparks, open flames and other ignition

sources. - No smoking.

P222 Do not allow contact with air.
P223 Do not allow contact with water.
P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/.../] equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 Wash hands [and ...] thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P231+P232 Handle under inert gas/... Protect from moisture.

P310 Immediately call a POISON CENTER or doctor/physician.

P363 Wash contaminated clothing before reuse.

P391 Collect spillage.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P334 IF ON SKIN: Immerse in cool water [or wrap in wet bandages].

P303+P361+P353 IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN

with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses if present and easy to do - continue rinsing.



14078 Meridian Parkway, Riverside, CA. 92518

P335+P334 Brush off loose particles from skin. Immerse in cool water/wrap in wet

bandages.

P370+P378 In case of fire: Use ... to extinguish.

P405 Store locked up.

P422 Store contents under ...

P402+P404 Store in a dry place. Store in a closed container.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Synonyms : n-BuLi;Butyl lithium;Butyllithium solution;Lithium-1-butanide;n-

Butyllithium;Butyllithium

Formula : C4H9Li Molecular weight : 64.06

Component	Classification	Concentration

n-Butyllithium solution

CAS-No.: 109-72-8 Self igniting liquid category 1; Category 1 of substances and mixtures

EC-No.: 203-698-7 that release flammable gases when exposed to water; Skin

corrosion/irritation category 1B; Severe eye injury/eye irritation category

1; H250, H260, H314, H318

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this material safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult



14078 Meridian Parkway, Riverside, CA. 92518

a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

no data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Dry powder Dry sand Unsuitable extinguishing media Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Carbon oxides Lithium oxides Combustible.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

no data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Do not flush with water.

6.4 Reference to other sections

For disposal see section 13.



14078 Meridian Parkway, Riverside, CA. 92518

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in cool place. Never allow product to get in contact with water during storage. Air & Moisture & Heat Sensitive, 2-8 °C, stored in argon.

7.3 Specific end use(s)

no data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Component	CAS No.	Value	Control parameters	Basis
pentane	109-66-0	PC-TWA	500 mg/m3	Occupational exposure limits for workplace hazards - chemical hazards
		PC-STEL	1000 mg/m3	Occupational exposure limits for workplace hazards - chemical hazards

8.2 Exposure controls

Appropriate engineering controls

Operate in accordance with industrial health and safety rules of use. Wash your hands before rest and at the end of work.

Personal protective equipment

Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU)

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Protective gloves against thermal risks The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.



14078 Meridian Parkway, Riverside, CA. 92518

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a fullface respirator with multipurpose combination (US) or type ABEK (EN 14387)

respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance
b) Odour
c) Odour Threshold
data available
no data available
no data available
no data available

e) Melting point/freezing point $-95\,^{\circ}\text{C}$ f) Initial boiling point and boiling range $80\,^{\circ}\text{C}$ g) Flash point $-21\,^{\circ}\text{C}$

h) Evaporation rate no data available i) Flammability (solid, gas) no data available

j) Upper/lower flammability or

explosive limits no data available k) Vapour pressure no data available l) Vapour density no data available

m) Relative density 0.693

n) Water solubility Miscible with diethyl ether and cyclohexane.

o) Partition coefficient: n-octanol/water no data available
p) Auto-ignition temperature no data available
q) Decomposition temperature no data available
r) Viscosity no data available
s) Explosive properties N no data available
t) Oxidizing properties N no data available

9.2 Other safety information

no data available



14078 Meridian Parkway, Riverside, CA. 92518

SECTION 10: Stability and reactivity

10.1 Reactivity

no data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Reacts violently with water.

10.4 Conditions to avoid

Heat, flames and sparks. Exposure to moisture.

10.5 Incompatible materials

Strong oxidizing agents, Reacts violently with water.

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

pentane

LD50 Oral - Rat - male and female - > 2.000 mg/kg (OECD Test Guideline 401) LC50 Inhalation - Rat - male and female - 4 h - > 25,3 mg/l (OECD Test Guideline 403) Remarks: (in analogy to similar products) The value is given in analogy to the following substances: cyclopentane

Skin corrosion/irritation

Skin - Rabbit Result: No skin irritation - 4 h (OECD Test Guideline 404) Causes skin irritation. (ECHA)

Serious eye damage/eye irritation

Eyes - Rabbit Result: No eye irritation (OECD Test Guideline 405) Causes serious eye damage.

Respiratory or skin sensitisation

Buehler Test - Guinea pig Result: negative (OECD Test Guideline 406)

Germ cell mutagenicity

Mutagenicity (mammal cell test): chromosome aberration. Chinese hamster ovary cells Result: negative Ames test Salmonella typhimurium Result: negative Mutagenicity (micronucleus test) Rat - male and female - Bone marrow

Result: negative

Carcinogenicity

no data available

Reproductive toxicity

no data available



14078 Meridian Parkway, Riverside, CA. 92518

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. - Central nervous system

Specific target organ toxicity - repeated exposure

no data available

Aspiration hazard

May be fatal if swallowed and enters airways. Aspiration hazard, Aspiration may cause pulmonary edema and pneumonitis.

Additional Information

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea

SECTION 12: Ecological information

12.1 Toxicity

pentane

Toxicity to fish static test LC50 - Oncorhynchus mykiss (rainbow trout) - 4,26 mg/l - 96 h (OECD Test Guideline 203) Toxicity to daphnia and other aquatic invertebrates static test EC50 - Daphnia magna (Water flea) - 2,7 mg/l - 48 h Remarks: (ECHA) Toxicity to algae static test ErC50 - Selenastrum capricornutum (green algae) - 10,7 mg/l - 72 h (OECD Test Guideline 201) static test NOEC - Selenastrum capricornutum (green algae) - 7,51 mg/l - 72 h (OECD Test Guideline 201)

12.2 Persistence and degradability

no data available

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

no data available

12.6 Other adverse effects

no data available

SECTION 13:

13.1 Disposal considerations

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Waste material must be disposed of in



14078 Meridian Parkway, Riverside, CA. 92518

accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 3394 Packing group: I Class: 4.2 (4.3)

Proper shipping name: Reportable Quantity(RQ): no data Poison Inhalation Hazard: no data

ORGANOMETALLIC SUBSTANCE, available available

LIQUID, PYROPHORIC, WATER-REACTIVE (pentane, Butyllithium) Environmental Hazards: no

IMDG

UN number: 3394 Packing group: I EMS-No: no data available Proper shipping name: ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE (pentane,

Butyllithium)

IATA

UN number: 3394 Packing group: I Class: 4.2 (4.3)

Proper shipping name: ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE (pentane,

Butyllithium)

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

SECTION 16: Other information

Regulatory Affairs

Prepared By ALADDIN SCIENTIFIC CORPORATION

Email: QualityAssurance@aladdinsci.com

Creation Date30-Nov-2023Revision Date10-Jan-2024Print Date11-Jan-2024

Revision Summary SDS sections updated v1



14078 Meridian Parkway, Riverside, CA. 92518

Disclaimer

Copyright Aladdin Co. Ltd. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Aladdin Co. Ltd. and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.