

SAFETY DATA SHEET

Version: v1
Revision Date: 2026-07-24
Print Date: 2026-07-24

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Xylene
Product Number : X1520947
Brand : aladdin
CAS-No. : 1330-20-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances.

1.3 Company

Company : ALADDIN SCIENTIFIC CORPORATION
Address : 14078 Meridian Parkway,
Riverside, CA. 92518
Telephone : +1 (833) 552-7181
Fax : no data available

1.4 Emergency telephone number

CHEMTREC®, Inside the USA : 1-800-424-9300
CHEMTREC®, Outside the USA :

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids : Category 3

Acute toxicity (Oral) : Category 5

Acute toxicity (Inhalation) : Category 4

Acute toxicity (Dermal) : Category 4

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation: Category 2A

Carcinogenicity : Category 2

Specific target organ toxicity - single exposure: Category 3 (respiratory tract irritation)

Specific target organ toxicity - repeated exposure: Category 2 (hearing organs)

Specific target organ toxicity - repeated exposure(Inhalation): Category 2 (Central nervous system, Liver, Kidney)

Aspiration hazard : Category 1 Short-term (acute) aquatic hazard: Category 2

Long-term (chronic) aquatic hazard: Category 3

2.2 GHS Label elements, including precautionary statements

Pictogram



Danger

Signal word

Hazard statement(s)

H226	Flammable liquid and vapor
H303	May be harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May causes damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects
H312+H332	Harmful in contact with skin or if inhaled

Precautionary statement(s)

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surface, sparks, open flames and other ignition sources. - No smoking.
P202	Do not handle until all safety precautions have been read and understood.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting/.../] equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash hands [and ...] thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P312	Call a POISON CENTER or doctor/... if you feel unwell.
P331	Do NOT induce vomiting.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
P303+P361+P353	IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
P332+P313	IF SKIN irritation occurs: Get medical advice/attention.
P337+P313	IF eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use ... to extinguish.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container to an approved waste disposal plant.
P304+P340+P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor. if you feel unwell.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Synonyms	: Xylene mixture of isomers Dimethylbenzene ksylen
Formula	: C8H10
Molecular weight	: 106.17

Component	Classification	Concentration
Ethylbenzene solution		
CAS-No. : 100-41-4 Flam. Liq. 2; Acute Tox. 4; STOT RE 2; Asp. Tox. 1; Aquatic Chronic 3;		
EC-No. : 202-849-4 H225, H332, H373, H304, H412		
Xylene		

Component	Classification	Concentration
CAS-No. : 1330-20-7 EC-No. :	Flammable liquids (Category 3), H226 Acute toxicity, Inhalation (Category 4), H332 Acute toxicity, Dermal (Category 4), H312 Skin irritation (Category 2), H315 Eye irritation (Category 2), H319 Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335 Specific target organ toxicity - repeated exposure (Category 2), hearing organs, H373 Specific target organ toxicity - repeated exposure, Inhalation (Category 2), Central nervous system, Liver, Kidney, H373 Aspiration hazard (Category 1), H304 Long-term (chronic) aquatic hazard (Category 3), H412	

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

Move the victim into fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration and consult a doctor immediately. Do not use mouth to mouth resuscitation if the victim ingested or inhaled the chemical.

In case of skin contact

Take off contaminated clothing immediately. Wash off with soap and plenty of water. Consult a doctor.

In case of eye contact

Rinse with pure water for at least 15 minutes. Consult a doctor.

If swallowed

Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Center immediately.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

no data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) foam dry powder

Unsuitable extinguishing media

There are no restrictions on extinguishing agents for this substance/mixture.

5.2 Special hazards arising from the substance or mixture

Oxocarbon Flammable Vapor is heavier than air, so it can diffuse along the ground. Forming explosive mixtures with air at high temperatures When a fire occurs, it may cause the generation of hazardous gases or vapors

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

no data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing mist, gas or vapours. Avoid contacting with skin and eye. Use personal protective equipment. Wear chemical impermeable gloves. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Prevent further spillage or leakage if it is safe to do so. Do not let the chemical enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Collect and arrange disposal. Keep the chemical in suitable and closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Operators should be specially trained and strictly abide by the operating procedures. Operation and disposal should be carried out in a place with local ventilation or general ventilation facilities. Avoid eye and skin contact and avoid breathing vapor. See Section 8 for personal protective measures. Keep away from fire and heat sources, and

smoking is strictly prohibited in the workplace. Use explosion-proof ventilation systems and equipment. If canning is required, the flow rate should be controlled, and there should be a grounding device to prevent the accumulation of static electricity. Avoid contact with incompatible substances such as oxidizing agents (see section 10 for incompatible substances). When handling, it should be lightly loaded and unloaded to prevent damage to packaging and containers. Empty containers may be harmful residues. Wash hands after use and prohibit eating or drinking in the workplace. Equipped with the corresponding variety and quantity of fire fighting equipment and leakage emer

7.2 Conditions for safe storage, including any incompatibilities

Tightly closed Drying. Store at room temperature.

7.3 Specific end use(s)

no data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. The selected protective gloves have to satisfy the specifications of Regulation (EU)2016/425 and the standard EN 374 derived from it.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a fullface particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the

sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

If safety requires, prevent further leakage or spillage. Do not let the product enter the sewer.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	form: Liquid color: Clear Colorless
b) Odour	no data available
c) Odour Threshold	no data available
d) pH	no data available
e) Melting point/freezing point	no data available
f) Initial boiling point and boiling range	137-140°C
g) Flash point	29°C
h) Evaporation rate	no data available
i) Flammability (solid, gas)	no data available
j) Upper/lower flammability or explosive limits	no data available
k) Vapour pressure	no data available
l) Vapour density	no data available
m) Relative density	0.86
n) Water solubility	no data available
o) Partition coefficient: n-octanol/water	no data available
p) Auto-ignition temperature	no data available
q) Decomposition temperature	no data available
r) Viscosity	no data available
s) Explosive properties N	no data available
t) Oxidizing properties N	no data available

9.2 Other safety information

no data available

SECTION 10: Stability and reactivity

10.1 Reactivity

no data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Exothermic reaction: Strong oxidant acid sulfur concentrated sulfuric acid Explosion/heat release hazardous reactants: nitric acid Uranium hexafluoride

10.4 Conditions to avoid

Heating

10.5 Incompatible materials

no data available

10.6 Hazardous decomposition products

In case of fire: see Section 5 Fire Extinguishing Measures

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity estimate inhalation -4 hours -12.25 mg/l - vapor (calculation method)

Symptoms: Possible symptoms: Mucosal irritation, cough, shortness of breath, possible damage: Damage to the respiratory tract

Acute toxicity estimated transdermal -1467 mg/kg (calculation method)

Skin corrosion/irritation

The mixture can cause skin irritation.

Serious eye damage/eye irritation

Mixtures can cause severe eye irritation

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

Specific target organ toxicity - single exposure

The mixture can cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Long term or repeated exposure to the mixture may cause organ damage. -Auditory organ Long term or repeated exposure to the mixture may cause organ damage. -Central nervous system, liver, kidney

Aspiration hazard

There is no data on inhalation hazards. Inhalation may cause Pulmonary edema and pneumonia.

Additional Information

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information**12.1 Toxicity****12.2 Persistence and degradability**

no data available

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

SECTION 13:**13.1 Disposal considerations****Product**

Recycle to process, if possible. Consult your local regional authorities and an expert of disposal. You may be able to dissolve or mix material with a combustible solvent and little by little burn in a chemical incinerator equipped with an afterburner and scrubber system. If a large amount of the substance is burned at a time, an explosion may occur.

Observe all federal, state and local regulations when disposing of the substance.

Contaminated packaging



Dispose of as unused product.

SECTION 14: Transport information

DOT (US)		
UN number: UN 1307	Packing group: III	Class: 3
Proper shipping name: XYLENES	Reportable Quantity(RQ):no data available	Poison Inhalation Hazard:no data available
Environmental Hazards: no		
IMDG		
UN number: UN 1307	Packing group: III	EMS-No:no data available
Proper shipping name: XYLENES		
IATA		
UN number: UN 1307	Packing group: III	Class: 3
Proper shipping name: XYLENES		

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

SECTION 16: Other information

Prepared By	Regulatory Affairs ALADDIN SCIENTIFIC CORPORATION Email: QualityAssurance@aladdinsci.com
Creation Date	24-Jul-2026
Revision Date	24-Jul-2026
Print Date	24-Jul-2026
Revision Summary	SDS sections updated v1

Disclaimer
Copyright Aladdin Co. Ltd. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Aladdin Co. Ltd. and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.